



Custom 1" Wood Blind

Model #WOOD1

The designer's choice for elegant, traditional window treatments.

PART I – GENERAL

1.01 SCOPE

A. Furnish and install Levolor blinds, provided by Levolor, 4110 Premier Drive, High Point, NC 27265, in accordance with specifications, drawings, and contract documents.

B. Related work specified elsewhere.

1.02 QUALITY ASSURANCE

A. Installer's qualifications:

1. The installer shall be a firm approved by Levolor's Contract Division.

2. The installer shall be qualified to install the product specified, as demonstrated by prior experience.

B. Job mock-up: (Describe)

1.03 SUBMITTALS

A. Product information: Submit Levolor's product literature and installation instructions.

B. Shop drawings: Indicate field-measured dimensions of opening which are to receive blinds, details on mounting surface and sill conditions, and details of corners and conditions between adjacent blinds.

C. Color samples: Submit a sample of each type and color of material specified.

1.04 DELIVERY, STORAGE, AND HANDLING

A. Packing and Shipping

1. Materials shall be delivered to the Project in Levolor's original unopened packaging with labels intact.

B. Storage:

1. Materials shall be stored in a clean area which is free of corrosive fumes, dust, and away from construction activities.

2. Materials shall be stacked horizontally using plastic or wood shims such that drainage and ventilation are provided for, and such that water cannot accumulate in, about or upon the containers.

3. Stacks shall be covered with tarpaulins or plastic such that ventilation is provided for, and such that contaminants are prevented from contacting surfaces.

1.05 PROJECT/SITE CONDITIONS (BEFORE PRODUCT INSTALLATION BEGINS)

A. Roof must be tight, windows and frames installed and glazed, and interior doors hung.

B. Wet work including concrete, masonry, plaster, stucco, terrazzo, sheetrock, spackling, and taping (including sanding) shall be complete and dry.

C. Ceilings, window pockets, electrical, and mechanical work above the product shall be complete.

D. Electrical power (110 volt AC) shall be available for installer's tools within 500 ft. of product installation areas.

1.06 WARRANTY

A. One Year Limited Warranty: Levolor Contract shall repair or replace for one year from the date of purchase of the blind, at its option, without charge, any part found defective in workmanship or material as long as the blind remains in the same window for which it was purchased.

PART II – PRODUCTS

2.01 MANUFACTURER AND PRODUCT DESCRIPTION:

A. Acceptable product Custom 1" Wood Blind manufactured by Levolor.

B. Materials:

1. Headrail shall be of .025" thick steel, "U" shaped, 1" high x 1-9/16" wide with flanged edges at top, and coated with baked on finish. All hardware shall be enclosed in the metal headrail.

2. Tilt Wand shall be of Hardwood with a .38" diameter, finished to match the slats of the blind.

3. Cord Lock shall be of .042" thick Tomized steel and shall be securely attached to headrail. It shall be a crashproof type with sufficient sensitivity to lock slats at desired height upon release of cords, or by swinging cords toward jamb while lowering slats. A revolving serrated cam shall gently snub all cords to hold the raised slats level at the desired height, increasing its grip for heavier loads.

4. Drum and cradle shall be provided for each ladder.

a. Drums shall be of .031" thick Tomized steel having two holes with rolled edges to anchor barbs of both ladder ends.

b. Cradles shall be of .042" thick Tomized steel having two holes with rolled edges to guide cords through bottom of headrail without abrasion. They shall provide bearing support for the tilt rod, thus preventing the weight of the blind from being transferred to the tilter. Cradles shall center drums over ladder openings.

c. Tilt Rod shall be a D-shaped Tomized steel rod with an average cross section of .28" designed to achieve minimum torsional deflection.

5. End Braces shall be of .037" thick Tomized steel with reinforcing ribs positively fastened to both ends of headrail. End braces shall incorporate a field adjustable tab to insure secure installation, center blind in window, and prevent lateral movement.

6. Installation Brackets shall be of at least .048" thick Tomized steel with baked-on finish to match headrail. The brackets shall incorporate a rivet-hinged safety locking front cover to permit removal of headrail without lateral movement. Mounting holes shall be located to accommodate overhead, side, or face mounting.

7. Intermediate Brackets shall be installed with blinds over 60" wide and under 80" long or over 55" and over 80" long. Brackets shall be supplied as required.

8. Ladders (slat supports) shall be braided polyester yarn dyed to Levolor color standard. The two vertical components shall be .076" x .038" designed for maximum flexibility combined with minimum stretch and tensile strength of not less than 50 lbs. per cable. Horizontal components (rungs) shall consist of not less than four cables inter-braided with the vertical components. Ladder shall support the slats without visible distortion. Distance between slats shall not exceed 21.5 mm (nominally 14.2 slats per vertical foot). Distance between ladders shall not exceed 23" for blinds up to 80" long. For blinds over 80" long, distance between ladders shall not be greater than 22". Distance between end ladder and end of slat shall not exceed 7".

9. Slats shall be of premium quality hardwood finished with a wood stain or solid coating selected from Levolor Custom colors, sealed, and lacquered. Maximum slat length is 96" to avoid material deflection. Standard 1" slats are nominally 1" wide. Slat thickness is nominally 1/8". Slats shall perform to 500 hours of 100% relative humidity testing, 300 hours of 5% salt spray solution at 95 degree F testing, and 250 hours of accelerated weathering testing without blistering, fading, corroding, or adhesive failure. Slat thickness and ladder support distances shall prevent visible sag or bow after continued use indoors.

10. Bottomrail shall be of solid wood, nominally 1" wide x 5/8" high and finished to coordinate with slats. Bottomrail shall have protective ladder caps designed to prevent bottom bar from marring window sill and/or mullions.

11. Lift Cord shall be braided of high strength, 1.4 mm dia. polyester fiber with a high tenacity polyester core, 34 picks per inch, 16 carrier smooth braids, and shall be flexible, have minimum stretch, maximum abrasion resistance characteristics, and a minimum breaking strength of 130 lbs. Cord shall be of sufficient length equalized to properly control raising and lowering of blind and spaced not over 46" between cords.

12. Options shall include:

- a. Cutouts
- b. Extension Brackets
- c. Hold-down Brackets
- d. Invisible Installation Brackets
- e. Multiple Blinds on One Headrail
- f. Multi-Colored Striping
- g. Pivot Plate
- h. Pocket Brackets
- i. Radius Corners
- j. Restrictive Cam Tilter
- k. Ring Pull
- l. Telescopic or Non-Telescopic Tilter Pole
- m. Top-lock Cord lock
- n. Universal Ring Tilter

PART III – EXECUTION

3.01 INSPECTION

A. Window treatment subcontractor shall be responsible for inspection of site, field measurements, and approval of mounting surfaces and installation conditions.

B. Subcontractor shall verify that site is free of conditions that interfere with blind installation and operation, and shall begin installation only when any unsatisfactory conditions have been rectified.

3.02 INSTALLATION

A. Installation shall comply with Levolor specifications, standards, and procedures.

B. Provide support brackets as per Levolor's installation instructions.

C. See installation instructions packaged with blinds for more installation details.

D. Provide adequate clearance to permit unencumbered operation of blind and hardware.

E. Demonstrate blinds to be in uniform and smooth working order.

3.03 CLEANING

A. Keep your Levolor Wood blinds looking their best by periodically wiping them with a soft, lightly dampened cloth, dusting mitt, or the round brush attachment from a vacuum cleaner.

Do not use solvents, abrasive solutions, or ultrasonic cleaners and equipment on your 1" Wood blinds which could cause damage to your blinds. The Warranty does not cover damage caused by cleaning methods that use abrasive solutions or ultrasonic cleaning machines.



Levolor Contract
4110 Premier Drive
High Point, NC 27265

Contract Customer Service
1-800-826-8021
www.levolorcontract.com

© Copyright 2004 Levolor. All rights reserved. US and non-US patents and patents pending. Product specifications are subject to change without notice. Printed in the USA.